

10 Rec'd PC 10.9 FEB 1998
09 / 01 1811
J. Williams
8-16-99

REMOTELY CONTROLLED GYROSTABILIZED OPERATOR CRANE

FIELD OF INVENTION

The invention relates to lifting machines, in particular to movie-operator crane which are arranged on various movable carriers: automobiles, ships, etc.

Prior Art

The closest solution in accordance with the technical subject matter is "REMOTELY CONTROLLED MOVIE-OPERATOR CRANE" (Inventor's Certificate of the U.S.S.R. No. 1,217,774) has a boom composed of telescopably connected movable and immovable sections, with the latter section hingedly mounted on a vertical support so as to vertically turn and connected with a vertical drive of the boom, wherein the vertical support is arranged on a base with the possibility of horizontal turning and connected to the drive of the horizontal turning, a first hinge link for arranging on it of a movie camera mounted on the movable section of the boom, a second and a third hinge link which form with the first hinge link and movable section a hinge-lever mechanism of a parrallogram type, wherein on a link which is parallel to the movable section the toothed rack is mounted cooperating with the drive of

BEST AVAILABLE COPY

000441.03090

extension of the movable section and mounted with the possibility of the axial movement in a housing hingedly mounted on the vertical support eccentrically relative to the axis of the hinge of mounting of the immovable section on the vertical support, and in the housing there is a drive for extension of the movable section which is kinematically connected with a counterweight movably mounted in the tail part of the movable section of the boom, a control board, electronic blocks of vertical and horizontal turning of the boom.

The above described remotely controlled operator crane has the following disadvantages:

1. Vibration of parts of the carrier on which it is arranged, as well as gaps of the drive of the mechanisms of crane and other movements of its construction cause substantial angular and rectilinear vibrations of the movie shooting equipment, which negatively effects the quality of the image.

2. Construction of hinge-lever parallelogram-type mechanism makes complicated assembly, increases weight of the crane and does not provide a vertical position of the hinge link during inclinations, swings and accelerations of the carrier, which disturbs the horizontal position of the frame with the use of any panoramic head for installation of the camera.

00041841.070699

3. Angular vibrations of the carrier are transmitted to the whole construction of the crane and cause increased load of the parts of the carrier, to which the crane is mounted, limit the possibility of the selection of the carrier and require reinforcement of its parts.

4. Rectilinear vibrations of the carriers are transmitted by the crane to the camera, which cause vibration of image even in the case of the use for shooting of gyrostabilized panoramic heads.

Summary of the Invention

The basis of the invention is an objective of creating such a remotely controlled gyrostabilized operator crane, in which the boom has an inner part formed with the possibility of turning along the axis of the boom, connected with the drive of the inner part of the boom and hinge link, while the mechanism of parallelogram-type includes a driving and a driven block connected by a cable, a gyroscopic sensitive element of hinge link is introduced and mounted on it so that its measuring axis is parallel to the axis of the extension of the hinge link, the gyroscopic sensitive element of the inner part of the boom is arranged so that its measuring axis is parallel to the axis of the boom, the gyroscopic sensitive element of the boom is mounted on it so that its measuring axis is parallel to the axis of the extension of the boom, the

00044841.030699

gyroscopic sensitive element of the vertical support is mounted on it so that its measuring axis is parallel to the axis of suspension of the vertical support relative to the base, longitudinal and vertical accelerometers are mounted on the hinge link so that their measuring axes and the axis of suspension of the hinge link are perpendicular, the transverse accelerometer is mounted on the inner part of the boom so that its measuring axis is parallel to the axis of suspension of the hinge link, electronic blocks of the hinge link and inner part of the boom, wherein the first input of the electronic block of the hinge link is connected with the output of the longitudinal accelerometer, the second input of the electronic block of the hinge link is connected with the output of the gyroscopic sensitive element of the hinge link, and the output of the electronic block of the hinge link is connected with the input of the drive of the hinge link, first input of the electronic block of the inner part of the boom is connected with the output of the transverse accelerometer, the second input of the electronic block of the inner part of the boom is connected with the output of the gyroscopic sensitive element of the inner part of the boom, the output of the electronic block of the inner part of the boom is connected with the input of the drive of the inner part of the boom, the first input of the electronic block of the vertical turning of the boom is connected with the output of the control board for vertical turning of the boom, the second input of the electronic block of the vertical turning of the boom is connected with the output of the gyroscopic sensitive element of the boom, the first input of the electronic block of the vertical turning of the boom

0001.134.0300

is connected with the output of the vertical accelerometer, and the output of the electronic block of the vertical turning of the boom is connected with the input of the vertical drive of the boom, the first input of the electronic block of the horizontal turning of the boom is connected with the output of the gyroscopic sensitive element of the vertical support, the second input of the electronic block of the horizontal turning of the boom is connected with the output of the control board for horizontal turning of the boom, the output of the electronic block of the horizontal turning of the boom is connected with the input of the drive of the vertical support, the vertical support of the boom, the drive of the inner part of the boom and the hinge link are mounted in a tail part of the boom and form a counterweight, to provide kinematic insulation of the hinge unit with the movie-television shooting equipment mounted on it from all angular vibrations of the carrier, its angular movements practically do not affect the movement of the shooting equipment, determined by the signals from the control board for controlling the crane, kinematic insulation of the boom from angular vibrations of the carrier around the vertical axis and the axis of suspension of the boom which during movement of the carrier makes possible to substantially reduce loads on it from the side of the base of the crane. Automation of the control process of the boom provides for a compensation of vertical rectilinear vibrations of the carrier in the point of mounting of the movie and television shooting equipment. As a result, the shooting equipment maintains its orientation regardless of the movement of the carrier and because

00010103030

Journal of Management Education 30(6)

[illegible][illegible]

parallel to the axis of suspension on the hinge link, a gyroscopic sensitive element of the inner part of the boom mounted on it so that its measuring axis is parallel to the axis of the boom, a gyroscopic sensitive element of the boom mounted on it so that its measuring axis is parallel to the axis of suspension of the boom, a gyroscopic sensitive element of a vertical support mounted on it so that its measuring axis is parallel to the axis of suspension of the vertical support relative to the base, longitudinal and vertical accelerometers mounted on the hinge link so that their measuring axes and the axis of suspension of the hinge link are mutually perpendicular, the transverse accelerometer mounted on the inner part of the boom so that its measuring axis is parallel to the axis of suspension of the hinge link, electronic blocks of the hinge link and the inner part of the boom, wherein the first input of the electronic block of the hinge link is connected with the output of the longitudinal accelerometer, the second input of the electronic block of the hinge link is connected with the output of the gyroscopic sensitive element of the hinge link, the output of the electronic block of hinge link is connected with the input of the drive of hinge link, the first input of the electronic block of the third part of the boom is connected with the output of the transverse accelerometer, the second input of the electronic block of the inner part of the boom is connected with the output of the gyroscopic sensitive element of the inner part of the boom, the output of the electronic block of the inner part of the boom is connected with the input of the drive of the inner part of the boom, the first input of the electronic block of the vertical turning of the

boom is connected with the output of the control board for vertical turning of the boom, the second input of the electronic block of the vertical turning of the boom is connected with the output of the gyroscopic element of the boom, the third input of the electronic block for the vertical turning of the boom is connected with the output of the vertical accelerometer, the output of the electronic block of the vertical turning of the boom is connected with the input of the vertical drive of the boom, the first input of the electronic block for the horizontal turning of the boom is connected with the output of the gyroscopic sensitive element of the vertical support, the second input of the electronic block for the horizontal turning of the boom is connected with the output of the control board for horizontal turning of the boom, the output of the electronic block of the horizontal turning of the boom is connected with the input of the drive of the vertical support, the vertical drive of the boom, the drive of the inner part of the boom and the hinge link are mounted in the tail part of the boom and perform the function of a counterweight.

Because of the use in the proposed remotely controlled gyrostabilized operator crane of the boom, containing the inner part formed with the possibility of turning along the axis of the boom, connected with the drive of the inner part of the boom, the boom mounted on the vertical support with the possibility of vertical turning and connected with the vertical drive of the boom, the vertical support mounted on the base with the possibility of the horizontal

00044341.070599

turning, connected with the horizontal drive of the vertical support, the hinge link for placing the movie and television equipment, mounted on the end of the inner part of the boom with the possibility of turning around the horizontal axis of the suspension of the hinge link, perpendicular to the axis of the boom, the mechanism of the parallelogram-type connected with the drive of the hinge link and composed of a driven and driving block connected by a cable, mounted in the tail part of the boom the vertical drive of the boom, the drives of the inner part of the boom, and the hinge link performing the functions of the counterweight, the control board and electronic blocks of vertical and horizontal turning of the boom, introduction of the gyroscopic sensitive element of the hinge link mounted on it so that its measuring axis is parallel to the axis of suspension of the hinge link, gyroscopic sensitive element of the inner part of the boom mounted on it so that its measuring axis is parallel to the axis of the boom, gyroscopic sensitive element of the boom mounted on it so that its measuring axis is parallel to the axis of suspension of the boom, gyroscopic sensitive element of the vertical support mounted on it so that its measuring axis is parallel to the axis of suspension of the vertical support relative to the base, longitudinal and vertical accelerometers mounted on the hinge link so that their measuring axes and the axis of suspension of the hinge link are mutually perpendicular, a transverse accelerometer mounted on the inner part of the boom so that its measuring axis is parallel to the axis of suspension of the hinge link, electronic blocks of hinge link and the inner part of the boom, connection

СССР - ТЕРМ

of the first input of the electronic block of the hinge link with the output of the longitudinal accelerometer, the second input of the electronic block of hinge link with the output of the gyroscopic sensitive element of the hinge link, the output of the electronic block of the hinge link with the input of the drive of the hinge link, connection of the first input of the electronic block of the inner part of the boom with the output of the transverse accelerometer, the second input of the electronic block of the inner part of the boom with the output of the gyroscopic sensitive element of the inner part of the boom, the output of the electronic block of the inner part of the boom with the input of the drive of the inner part of the boom, connection with the first input of the electronic block for the vertical turning of the boom with the output of the control board for the vertical turning of the boom, the second input of the electronic block of the vertical turning of the boom with the output of the gyroscopic sensitive element of the boom, the first input of the electronic block of the vertical turning of the boom, with the output of the vertical accelerometer, the output of the electronic block of the vertical turning of the boom with the input of the vertical drive of the boom, connection of the first input of the electronic block of the horizontal turning of the boom with the output of the gyroscopic sensitive element of the vertical support, the second input of the electronic block of the horizontal turning of the boom with the output of the control board for the horizontal turning of the boom, the output of the electronic block of the horizontal turning of the boom with the input of the drive of the vertical support, there are provided a four-axes

gyrostabilization for the proposed construction of the movie operator crane, or in other words its hinge unit with the movie and television shooting equipment, the boom, its inner part and the vertical support, substantial simplifications and weight reduction of the construction and because of this obtaining of stable and qualitative image with ensuring of a horizontal frame, as well as substantial expansion of operator possibilities.

The invention is illustrated by a diagram.

Short Description of Diagram

Electronic-kinematic diagram of the remotely controlled gyrostabilized operator crane is shown in Figure 1.

The remotely controlled gyrostabilized operator crane contains a boom 1 composed of an inner part 2 formed with the possibility of turning in bearings 3, 4 along the axis of the boom 5, connected with the drive of the inner part of the boom 6. The boom 1 is mounted on the vertical support 7 with the possibility of the vertical turning in the bearings 8, 9 around the axis of the boom 10 and connected with the vertical drive of the boom 11, wherein the vertical support 7 is mounted on the base 12 arranged on the carrier 13 with the possibility of horizontal turning in the bearing 14 around the axis of suspension

of the vertical support 15 and connected with the drive of the vertical support 16. The hinge link 17 for placing a movie and television shooting equipment 18 mounted on the end of the inner part of the boom 2 with the possibility of turning around the axis of suspension of the hinge link 19 in the bearing 20 perpendicular to the axis of the boom 5, connected with the drive of the hinge link 21 by a mechanism of a parallelogram-type 22 composed of a driving and driven blocks 23, 24 connected by a cable 25 mounted in the tail part of the inner part of the boom 2, a vertical drive of the boom 11, drives of inner parts of the boom 6 of the hinge link 17 mounted in the tail part of the inner part of the boom 2 performed partially the function of the counterweight 6.

The gyroscopic sensitive element of the hinge link 27 is mounted on the hinge link 17 so that its measuring axis is parallel to horizontal axis of the suspension of the hinge link 19, the longitudinal and vertical accelerometer 28, 29 are mounted on the hinge link 17 so that their measuring axes and the axes of the suspension of the hinge link 19 are mutually perpendicular, the gyroscopic sensitive element of the inner part of the boom 30 mounted on the inner part of the boom 2 so that its measuring axis is parallel to the axis of the boom 5, the transverse accelerometer 21 mounted on the inner part of the boom 2 so that its measuring axis is parallel to the axis of suspension of the hinge link 19, the gyroscopic sensitive element of the boom 32 mounted so that its measuring axis is parallel to the axis of the suspension of the boom 10, the

00011841-070599

gyroscopic sensitive element of the vertical support 33 mounted on the vertical support 7 so that its measuring axis is parallel to the axis of suspension of the vertical support 15.

The control board 34 provided for forming in the first output 35 of a signal for controlling the horizontal turning of the boom around an axis of suspension of the vertical support 15 and in the second output 36 of a signal for controlling of the vertical turning of the boom around the axis of suspension of the boom 10.

The electronic block for horizontal turning of the boom 37 has two inputs, the first input 38 is connected with the output of the gyroscopic sensitive element of the vertical support 33, the second input 39 is connected with the output of the control board 35, and the output is connected with the drive of the vertical support 16.

The electronic block of the vertical turning of the boom 40 has three inputs, the first input 41 is connected with the second output of the control board for the vertical turning of the boom 36, the second input 42 is connected with the output of the gyroscopic sensitive element of the boom 32, the third input 43 is connected with the output of the vertical accelerometer 29, and the output is connected with the input of the vertical drive of the boom 11.

00011041 070590

The electronic block of the inner part of the boom 44 has two inputs, the first input 45 is connected with the output of the transverse accelerometer 31, the second input 46 is connected with the output of the gyroscopic sensitive element of the inner part of the boom 30, and the output is connected with the drive of the inner part of the boom 36.

The electronic block of the hinge link 47 has two inputs, the first input 48 is connected with the output of the longitudinal accelerometer 28, the second input 49 is connected with the output of the gyroscopic sensitive element of the hinge link 27, and the output is connected with the input of the drive of the hinge link 21.

The remotely controlled gyrostabilized operator crane operates in the following manner.

When there are no signals from the control board 34, the possibility of turning of the movie and television shooting equipment 8 and the elements of the construction of the crane exists only as a result of action on them by external disturbing movements, for example friction in the bearings and drives, disbalance, aerodynamic forces, stretching of current conductors, etc. Therefore for stabilization of the position of the hinge link 17 and the shooting equipment 18 arranged on it, it is necessary that, by means of the

0004494.0309

gyroscopic sensitive elements 32, 27, 30, 31 of the boom 1, the hinge link 27, the inner part of the boom 30, the vertical support 33, the electronic block of the horizontal and vertical turning of the boom 37, 40, the inner part of the boom 44, the hinge link 47 and the drives 16, 11, 6, 21, to apply to corresponding elements of the crane the moments which compensate the above listed outer disturbing moments.

With the action on the hinge link 13 of the moment of outer surface around the axis of suspension of the hinge link 19, the gyroscopic sensitive element of the hinge link 27 generates a signal which is supplied to the second input of the electronic block of the hinge link 49. This signal is amplified by this block, and from its outlet is supplied to the input of the drive of the hinge link 21. The obtained moment, by means of the mechanism of the parallelogram type 22 containing the driving block 23, the cable 25, and the driven block 24. Is transmitted to the hinge link 17 and compensates the moment of the outlet forces, so as to provide the immovability of the movie and television equipment 18.

With the action on the hinge link 17 of the moment of outer forces around the axis of the boom 5, it is transmitted through the bearing 20 to the inner part of the boom, the gyroscopic sensitive element of the inner part of the boom 30 generates a signal which is supplied to the second input of the

000134 070699

electronic block of the inner part of the boom 46. This signal is amplified by this block, and from its output is supplied to the input of the drive of the inner part of the boom 6. The obtained moment, through the bearing 20, is supplied through the hinge link 17 and compensates the moment of the outer forces, so as to prevent the change of the position of the hinge link 17 in the space around the axis of suspension of the inner part of the boom 5 so as to provide the immovability of the movie and television shooting equipment 18.

With the action of the moment of the outer forces on the boom 1 around the axis 10, the gyroscopic sensitive element of the boom 32 generates a signal which is supplied to the second input 42 of the electronic block for the vertical turning of the boom 40. This signal is amplified by this block, and from its output is supplied to the input of the vertical drive of the boom 11. The moment generated by the drive 11 compensates the moment of the outer forces, so as to prevent vibration of the boom 1 around the axis 10.

With the action of the moment of outer forces on the boom 1 around the axis 15, it is transmitted through the bearings 8, 9 to the vertical support 7. The gyroscopic sensitive element of the boom 33 generates the signal which is supplied to the first input 38 of the electronic block of the horizontal turning of the boom 37. This signal is amplified by this block, and from its output is supplied to the input of the drive of the vertical support 16.

The moment generated by the drive compensates the moment of the outer forces so as to prevent vibrations of the boom 1 around the axis 18.

Therefore, in the absence of signals from the control board 34, the moments of the outer forces applied to the movie shooting equipment 18 around the axes 5 and 19, and also to the boom around the axes 10 and 15 are compensated which allows to exclude vibrations of the shooting equipment 18 and the boom 1.

With the supply from the second output 36 of the control board 34 of a signal for controlling the boom 1 around the axis 10 to the first input 41 of the electronic block for the vertical turning of the boom 40, it is added to the output signal of the gyroscopic sensitive element of the boom 32 supplied to the first input of the electronic block 40.

As a result, in the block 40 a signal is formed which corresponds to the turning of the coordinate system, modeled by the gyroscopic sensitive element of the boom 32. This signal is supplied to the input of the vertical drive of the boom 11, which turns the boom 1 around the axis of suspension of the boom 10 in exact correspondence to the signal and to the first output 36 of the control board 34.

0004404.03000

With the supply from the first output 35 of the control board 34 of the signal for controlling of the boom 1 around the axis 15 to the second input 39 of the electronic block of the horizontal turning of the booms 37, it is added to the output signal of the gyroscopic sensitive element of the vertical support 33 supplied to the first input 38 of the above mentioned electronic block. As a result, at the output of this block 37 a signal is formed which corresponds to the turning of the coordinate system modeled by the gyroscopic sensitive element of the vertical support 33. This signal is supplied to the input of the drive of the vertical support 16, which turns the boom 1 around the axis 15 in exact correspondence with the signal and the first output 35 of the control board 34.

The inaccuracies of the gyroscopic sensitive element of the inner part of the boom 30, the electronic block of the inner part of the boom 44, and also outer disturbing moments applied to the hinge link 17 and the inner part of the boom 2 around the axis of the boom 5 during a long time interval can cause its turning around this axis. In order to exclude this turning, the transverse accelerometer 31 is arranged and measures the deviation of the axis of the suspension of the hinge link 19 from the surface of the horizon. From the output, the signal is supplied to the first input 45 of the electronic block of the inner part of the boom 44 and is added to the signal at the second input 46 of the block 44 so as to cause turning of the coordinate system modeled by the gyroscopic sensitive element of the inner part of the boom 30 toward the side

0001404.03099

which is opposite to the deviation of the axis of suspension of the hinge link 19 from the plane of horizon. At the output of the electronic block of the inner part of the boom 44, a signal is formed which is supplied to the input of the drive of the inner part of the boom 44, which turns it and the axis of suspension of the hinge link 19 to the plane of horizon.

Inaccuracies of the gyroscopic sensitive element of the hinge link 27, the electronic block of the hinge link 47 and also outer disturbing moments applied to the shooting equipment 18 and hinge link 17 around its hinge link 19 over a long time interval can cause turning of these elements around the axis 19. For excluding this turning, a longitudinal accelerometer 28 is arranged and measures the deviation of the hinge link 17 from the plane of horizon around the axis of suspension of the hinge link 19. With the mentioned deviation the signal from the input of the longitudinal accelerometer 28 is supplied to a first input 48 of the electronic block of the hinge link 47 and is added to the signal of the second input 49 of the gyroscopic sensitive element of the hinge link 27 so as to cause turning of the coordinate system modeled by this sensitive element toward the side which is opposite to the deviation of the hinge link 17 from the plane of horizon. At the output of the electronic block of the hinge link 47 a signal is formed which is supplied to the input of the drive of the hinge link 21, which by the mechanism of parallelogram type 22 containing the driving

000144.0369
000000.0000

•

7th. 10th. 11th. 12th.

1. The first group of people who are not in the labor force are those who are not in the labor force because they are not in the labor force.

6121

1142. 1. 10. 1951

3 3 1 0 1 1 1 1 1 1

ally parlor

2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 104

Journal of Management Education

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ BLACK BORDERS

☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☐ FADED TEXT OR DRAWING

☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☒ LINES OR MARKS ON ORIGINAL DOCUMENT

☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.